

Specification Sheet NITROGEN DIOXIDE 4 SE 5 V

Sensor Type NO2 4 SE 5 V

Detectable Gases NO2 Nitrogen Dioxide

Part Number 01-34-50-02

Measuring Principle 3-electrode sensor

Specific Sensor Data no

Connector 4 pin socket connector



Long Term Sensitivity Drift < 1 % / month
Deviation from linearity at standard range < 10 % FS

Zero voltage at normal conditions 200 mV (± 10 mV) shifted for Offset

Sensitivity ~ 48 mV/ppm
Output Range 0 to 5 V
Supply Voltage 6 to 12 V

Response time at target level


T50 < 3 s
T90 < 10 s
Sensor warm up time typically 10 min


Operating conditions - 20°C ... +60°C


15 ... 90 % r. h.
Sensor life time 5 years expected

Sensor dimensions Ø 20,3 mm: Height 26,5 mm

Dimensions Solidsense sensor 4 SE (all dimensions in mm ± 0,15 mm tolerance)







Other Detection Ranges on Request





Specification Sheet NO₂ 4 SE 5 V

Cross Sensitivity

Gas	Formula	Test Gas Concentration	Reading in ppm
Ammonia	NH3	25 ppm	0
Carbon Dioxide	CO2	5000 ppm	0
Carbon Monoxide	CO	30 ppm	0
Chlorine	CI2	1.0 ppm	0
Hydrocarbons unsaturated	-	1 %	0
Hydrogen	H2	100 ppm	0
Hydrogen Sulphide	H2S	10 ppm	?
Isopropanol	C3H7OH	1000 ppm	0
Nitric Oxide	NO	20 ppm	0
Chlorine Dioxide	CIO2	1 ppm	1
Ozone	O3	0.5 ppm	?
Sulphur Dioxide	SO2	20 ppm	?

Please Note: Test conditions at 20°C/ 1013 hPa, Flow Rate > 500 qcm/min Cross sensitivity gases are not target gases. Relation can change with aging.

Solidsense GmbH believes the data contained herein are factual, and the opinions expressed are of qualified experts regarding the results of tests conducted, the data are not to be taken as warranty or representation which Solidsense assumes legal responsibility. The data are offered solely for consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with federal, state, and local laws and regulations. Specifications are subject to change without notice.

Rev. 11-05-31