

## Specification Sheet OXYGEN SECS

Sensor Type SECS 02 25 Sensor

Detectable Gases O2 Oxygen

PN wafer à 48 01-01-30-01

sensors

PN single sensor 01-02-30-01 *Amperometric* Measuring Principle

3-electrode sensor

Specific Sensor Data

Connector 3 gold contacts



0.0 - 30.0 Vol.%Standard Range

Lower Detectable Limit (LDL) 0.1 Vol.% Maximum Range 50 Vol.%

-400 to -600 mV Bias voltage

MAK/TLV

Long Term Sensitivity Drift < 0.1 Vol.% / month

Deviation from linearity at standard range < 5 % FS Current at 21 Vol.% Oxygen  $7 - 11 \mu A$ 

Sensitivity ~ 0,04 nA ppm

Response time at target level

Operating conditions

T50 < 5 s

T90 < 15 s

Sensor warm up time typically 10 min (10 s)

(pre-powered) - 20°C ... +50°C

15 ... 90 % r. h.

< 0,3 %/°C Temperature dependence

Sensor life time 3 years expected

Sensor dimensions 10 mm x 8,8 mm x 4 mm



## Specification Sheet Oxygen

## **Cross Sensitivity**

Gas	Formula	Test Gas Concentration	Reading in %
Ammonia	NH3	100 ppm	0.0
Carbon Dioxide	CO2	5000 ppm	0.0
Carbon Monoxide	CO	60 ppm	0.0
Chlorine	Cl2	1.0 ppm	0.0
Hydrocarbons unsaturated	-	1 %	0.0
Hydrogen	H2	100 ppm	0.0
Hydrogen Sulphide	H2S	10 ppm	0.0
Isopropanol	C3H7OH	1000 ppm	0.0
Nitric Oxide	NO	20 ppm	0.0
Nitrogen Dioxide	NO2	10 ppm	0.0
Ozone	O3	0.5 ppm	0.0
Sulphur Dioxide	SO2	20 ppm	0.0

**Please Note:** Test conditions at 20°C/ 1013 hPa, Flow Rate > 500 qcm/min Cross sensitivity gases are not target gases. Relation can change with aging.

Solidsense GmbH believes the data contained herein are factual, and the opinions expressed are of qualified experts regarding the results of tests conducted, the data are not to be taken as warranty or representation which Solidsense assumes legal responsibility. The data are offered solely for consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with federal, state, and local laws and regulations. Specifications are subject to change without notice.

Rev 10-11-15