

R-T 分度表

R <sub>(25℃)</sub> : 40.27KΩ					B <sub>25/50</sub> : 3950				
T(°C)	R(KΩ)	T(°C)	R(KΩ)	T(°C)	R(KΩ)	T(°C)	R(KΩ)	T(°C)	R(KΩ)
-50	2644.8	-15	283.26	20	48.944	55	12.004	90	3.6867
-49	2391.3	-14	268.22	21	46.982	56	11.571	91	3.5734
-48	2205.7	-13	254.02	22	45.082	57	11.154	92	3.4647
-47	2045.4	-12	240.61	23	43.485	58	10.752	93	3.3601
-46	1898.5	-11	227.92	24	41.836	59	10.365	94	3.2596
-45	1775.7	-10	215.93	25	40.270	60	9.9910	95	3.1628
-44	1654.6	-9	202.43	26	38.551	61	9.6385	96	3.0695
-43	1554.8	-8	190.84	27	36.927	62	9.3007	97	2.9796
-42	1459.5	-7	180.70	28	35.325	63	8.9769	98	2.8928
-41	1382.0	-6	171.64	29	33.638	64	8.6663	99	2.8090
-40	1297.9	-5	163.42	30	32.127	65	8.3681	100	2.7279
-39	1223.7	-4	155.81	31	30.817	66	8.0817	101	2.6494
-38	1149.1	-3	148.66	32	29.573	67	7.8066	102	2.5735
-37	1075.8	-2	141.86	33	28.386	68	7.5420	103	2.4998
-36	1005.1	-1	135.32	34	27.250	69	7.2875	104	2.4284
-35	937.89	0	128.98	35	26.159	70	7.0424	105	2.3590
-34	874.76	1	122.58	36	25.111	71	6.8064	106	2.2933
-33	816.05	2	116.80	37	24.102	72	6.5788	107	2.2293
-32	761.86	3	110.93	38	23.133	73	6.3594	108	2.1672
-31	712.19	4	105.20	39	22.202	74	6.1476	109	2.1068
-30	666.91	5	99.628	40	21.311	75	5.9430	110	2.0481
-29	625.82	6	94.502	41	20.460	76	5.7468	111	1.9912
-28	588.68	7	89.895	42	19.649	77	5.5589	112	1.9360
-27	555.21	8	85.680	43	18.881	78	5.3788	113	1.8825
-26	525.15	9	81.765	44	18.157	79	5.2060	114	1.8306
-25	498.22	10	78.080	45	17.477	80	5.0402	115	1.7803
-24	469.60	11	74.576	46	16.816	81	4.8809	116	1.7317
-23	443.01	12	71.221	47	16.184	82	4.7278	117	1.6847
-22	418.23	13	67.996	48	15.580	83	4.5805	118	1.6392
-21	395.08	14	64.891	49	15.003	84	4.4387	119	1.5953
-20	373.42	15	61.903	50	14.449	85	4.3020	120	1.5528
-19	353.11	16	59.036	51	13.919	86	4.1703		
-18	334.04	17	56.296	52	13.411	87	4.0431		
-17	316.09	18	53.693	53	12.923	88	3.9203		
-16	299.19	19	51.239	54	12.455	89	3.8016		