



HUMIDITY



TEMPERATURE



FLOW



CONDUCTIVITY

# HYT 939

## Digital Humidity and Temperature Module

Optimal for extremely sophisticated, industrial applications




INNOVATIVE SENSOR TECHNOLOGY

### Benefits & Characteristics

- Calibrated and temperature compensated
- High chemical resistance
- Wide humidity and temperature range
- Very stable at high humidity
- Mechanically robust
- Excellent humidity/temperature accuracy and stability
- I<sup>2</sup>C protocol (address 0x28 or alternative address)
- Very low drift
- Interchangeable without adjustments
- Pressure-resistant version up to 16 bars upon request

### Illustration<sup>1)</sup>



<sup>1)</sup> For actual size, see mechanical dimensions

### Technical Data

Operating temperature range:	-40 °C to +125 °C
Operating humidity range:	0 % RH to 100 % RH
Hysteresis:	< ±1 % RH
Linearity error:	< ±1 % RH
Temperature error:	0.05 % RH/K (0 °C to +60 °C)
Operating voltage:	2.7 V to 5.5 V
Current consumption (nominal):	< 22 µA at 1 Hz measuring rate; 850 µA max.
Current consumption (sleep):	< 1 µA
Digital interface:	I <sup>2</sup> C, address 0x28 or alternative address
Operating voltage (limits):	-0.3 V to 6 V
Storage conditions:	-20 °C to +50 °C

	Humidity	Temperature
Accuracy:	±1.8 % RH at +23 °C (0 % RH to 90 % RH)	±0.2 K (0 °C to +60 °C)
Reproducibility:	±0.2 % RH	±0.1 K
Resolution:	0.02 % RH	0.015 °C
Response time $t_{63}$ :	< 10 s with metal mesh filter	< 10 s with metal mesh filter
Long-term drift:	< 0.5 % RH/a	< 0.05 K/a
Measuring principle:	Capacitive polymer humidity sensor	PTAT (integrated)




# HYT 939

## Digital Humidity and Temperature Module




Optimal for extremely sophisticated, industrial applications

### Mechanical Dimensions



### Pin Assignment



1	2	3	4
SCL	VCC	GND	VDA

### Order Information

Order code	HYT 939 150.00067
------------	----------------------

### Additional Electronics

LabKit:	DHHYTLabKit_E
LCD module:	DHLCD-Modul_E
	Document name:



HUMIDITY



TEMPERATURE



FLOW



CONDUCTIVITY

# HYT 939

## Digital Humidity and Temperature Module

Optimal for extremely sophisticated, industrial applications



INNOVATIVE SENSOR TECHNOLOGY

### Additional Documents

---

Application Note:

Document name:

AHHYTM\_E



INNOVATIVE SENSOR TECHNOLOGY

Innovative Sensor Technology IST AG, Stegrütistrasse 14, CH-9642 Ebnat-Kappel, Switzerland,  
Phone: +41 (0) 71 992 01 00 | Fax: +41 (0) 71 992 01 99 | E-mail: [info@ist-ag.com](mailto:info@ist-ag.com) | Web: [www.ist-ag.com](http://www.ist-ag.com)



All mechanical dimensions are valid at 25 °C ambient temperature, if not differently indicated • All data except the mechanical dimensions only have information purposes and are not to be understood as assured characteristics • Technical changes without previous announcement as well as mistakes reserved • The information on this data sheet was examined carefully and will be accepted as correct; No liability in case of mistakes • Load with extreme values during a longer period can affect the reliability • The material contained herein may not be reproduced, adapted, merged, translated, stored, or used without the prior written consent of the copyright owner • Typing errors and mistakes reserved • Product specifications are subject to change without notice • All rights reserved