



Standard Low Pass Filters

RLC Electronics' Standard Low Pass Filters are available with cut off frequencies ranging from 100MHz to 18 GHz. These filters combine minimum insertion loss and low VSWR in the Pass Band, together with sharp skirt selectivity and high rejection in the Stop Band. This is accomplished by the utiliza-

tion of multi-sectional, modern network design. Miniaturization of these units is accomplished by utilizing advanced coaxial techniques and optimum selection of materials. Both lumped constant and distributive techniques are utilized in the fabrication of these filters.

Specifications

F-1-2-3

Model Number	Pass Band (MHz)	3 dB Point (Typical) (MHz)	30 dB Point (Typical) (MHz)	60 db (Min.) Stop Band	Insertion Loss dB Max. Pass Band
F-10-100	DC-100	125	150	180-500	.45
F-10-200	DC-200	250	300	360-1000	.35
F-10-300	DC-300	375	450	540-1500	.35
F-10-400	DC-400	500	600	720-2000	.25
F-10-500	DC-500	625	750	900-2500	.25
F-10-600	DC-600	750	900	1080-3000	.25
F-10-800	DC-800	1000	1200	1440-4000	.25
F-10-1000	DC-1000	1250	1500	1800-5000	.25
F-10-1500	DC-1500	1875	2250	2700-7500	.25
F-10-2000	DC-2000	2500	3000	3600-10000	.25
F-10-3000	DC-3000	3750	4500	5400-15000	.25
F-10-4000	DC-4000	5000	6000	7200-20000	.35
F-10-5000	DC-5000	6250	7500	9000-25000	.35
F-30-600	DC-600	630	720	810-3000	.45
F-30-800	DC-800	840	960	1080-4000	.45
F-30-1000	DC-1000	1050	1200	1350-5000	.45
F-30-1500	DC-1500	1575	1800	2025-7500	.45
F-30-2000	DC-2000	2100	2400	2700-10000	.25
F-30-3000	DC-3000	3150	3600	4050-15000	.25
F-30-4000	DC-4000	4200	4800	5400-20000	.35
F-30-5000	DC-5000	5250	6000	6750-25000	.35
F-30-6000	DC-6000	6300	7200	8100-30000	.35
F-30-7000	DC-7000	7350	8400	9450-35000	.35
F-30-8000	DC-8000	8400	9600	10800-40000	.35
F-30-10.0	DC-10000	10500	12000	13500-40000	.35
F-30-12.4	DC-12400	13000	14900	16740-40000	.45
F-30-18.0	DC-18000	18900	21600	24300-40000	.45

Pass Band VSWR: 1.35:1 to 8 GHz

1.45:1 to 12.4 GHz

1.55:1 to 18.0 GHz

Power Rating: 50 Watts Average

Impedance: 50 Ohms

Connectors: (Male & Female)

Environmental: MIL-E-5400, Class 1A

Except Op temp. range -55C to +85C

Connector Types: (Male & Female)

Type - Recommend Frequency Range:

N DC - 12,400

BNC DC - 1,000

TNC DC - 15,000

SMA DC - 26,000

To designate the filter desired use:

- (1) 10 or 30 for model number
(2) 100, 200 etc for cutoff frequency

- (3) "N" for type N, "B" for BNC, "T" for TNC or "R" for SMA connectors. Add "M" or "F" for two male or female.





Example: F-30-1000-NF is a model 30, 1000 MHz cutoff with type N female connectors




RLC ELECTRONICS, INC.

83 Radio Circle, Mount Kisco, New York 10549 • Telephone: 914-241-1334 • Fax: 914-241-1753
<http://www.rfoe.net/> TEL:0755-83397033 FAX:0755-83376182 E-MAIL:szss20@163.com
 e-mail: sales@rlcelectronics.com • www.rlcelectronics.com

Typical Operating Curves



Outline Drawing



MODEL	A			B		WEIGHT* (OUNCES)
	N	BNC/TNC	SMA	N.BNC TNC	SMA	
F-30-800	6.51	5.93	5.54	.50	.50	4.5
F-30-800	5.57	5.34	4.95	.50	.50	4.0
F-30-1000	5.28	5.01	4.62	.50	.50	3.0
F-30-1500	4.80	4.53	4.14	.50	.50	3.5
F-30-2000	7.00	6.93	6.48	.44	.44	3.5
F-30-3000	5.31	5.09	4.76	.44	.44	3.0
F-30-4000	4.44	4.23	3.90	.44	.44	2.5
F-30-5000	4.14	3.96	3.76	.44	.31	1.5
F-30-6000	3.92	3.67	3.12	.44	.31	1.5
F-30-7000	3.60	2.56	3.25	.44	.31	1.5
F-30-8000	3.40	3.06	2.94	.44	.31	1.5
F-30-10.0	3.35	3.28	2.68	.44	.31	1.0
F-30-12.4	3.12	2.90	2.13	.44	.31	1.0
F-30-18.0	—	—	1.61	—	.25	1.0

*Type SMA connector

MODEL	A			B		WEIGHT* (OUNCES)
	N	BNC/TNC	SMA	N.BNC TNC	SMA	
F-10-100	6.65	6.42	6.03	.50	.50	5.0
F-10-200	5.02	4.78	4.39	.50	.50	4.5
F-10-300	4.08	3.84	3.45	.50	.50	4.0
F-10-400	3.82	3.57	3.19	.50	.50	4.0
F-10-500	4.62	4.37	3.98	.50	.50	3.5
F-10-600	4.31	4.06	3.67	.50	.50	3.5
F-10-800	3.94	3.70	3.31	.50	.50	3.5
F-10-1000	3.72	3.53	3.14	.50	.50	3.0
F-10-1500	3.49	3.53	2.88	.50	.50	2.5
F-10-2000	6.00	5.40	4.96	.44	.44	2.5
F-10-3000	4.15	4.40	3.87	.44	.44	2.0
F-10-4000	4.00	3.48	3.17	.44	.44	2.0
F-10-5000	3.15	3.40	2.76	.44	.31	2.0

Tolerances unless otherwise specified are: .xx, $\pm .02$; .xxx, $\pm .005$.



RLC ELECTRONICS, INC.

83 Radio Circle, Mount Kisco, New York 10549 • Telephone: 914-241-1334 • Fax: 914-241-1753
 83467 射频通信 <http://www.rfoe.net/> TEL: 0755-83397033 FAX: 0755-83376182 E-MAIL: szsss20@163.com
 e-mail: sales@rlcelectronics.com • www.rlcelectronics.com

SUNSTAR 商斯达实业集团是集研发、生产、工程、销售、代理经销、技术咨询、信息服务等为一体的高科技企业，是专业高科技电子产品生产厂家，是具有 10 多年历史的专业电子元器件供应商，是中国最早和最大的仓储式连锁规模经营大型综合电子零部件代理分销商之一，是一家专业代理和分销世界各大品牌 IC 芯片和电子元器件的连锁经营综合性国际公司，专业经营进口、国产名厂名牌电子元件，型号、种类齐全。在香港、北京、深圳、上海、西安、成都等全国主要电子市场设有直属分公司和产品展示展销窗口门市部专卖店及代理分销商，已在全国范围内建成强大统一的供货和代理分销网络。我们专业代理经销、开发生产电子元器件、集成电路、传感器、微波光电元器件、工控机/DOC/DOM 电子盘、专用电路、单片机开发、MCU/DSP/ARM/FPGA 软件硬件、二极管、三极管、模块等，是您可靠的一站式现货配套供应商、方案提供商、部件功能模块开发配套商。商斯达实业公司拥有庞大的资料库，有数位毕业于著名高校——有中国电子工业摇篮之称的西安电子科技大学（西军电）并长期从事国防尖端科技研究的高级工程师为您精挑细选、量身订做各种高科技电子元器件，并解决各种技术问题。

微波光电部专业代理经销高频、微波、光纤、光电元器件、组件、部件、模块、整机；电磁兼容元器件、材料、设备；微波 CAD、EDA 软件、开发测试仿真工具；微波、光纤仪器仪表。欢迎国外高科技微波、光纤厂商将优秀产品介绍到中国、共同开拓市场。长期大量现货专业批发高频、微波、卫星、光纤、电视、CATV 器件：晶振、VCO、连接器、PIN 开关、变容二极管、开关二极管、低噪晶体管、功率电阻及电容、放大器、功率管、MMIC、混频器、耦合器、功分器、振荡器、合成器、衰减器、滤波器、隔离器、环行器、移相器、调制解调器；光电子器件和组件：红外发射管、红外接收管、光电开关、光敏管、发光二极管和发光二极管组件、半导体激光二极管和激光器组件、光电探测器和光接收组件、光发射接收模块、光纤激光器和光放大器、光调制器、光开关、DWDM 用光发射和接收器件、用户接入系统光收发器件与模块、光纤连接器、光纤跳线/尾纤、光衰减器、光纤适配器、光隔离器、光耦合器、光环行器、光复用器/转换器；无线收发芯片和模组、蓝牙芯片和模组。

更多产品请看本公司产品专用销售网站：

商斯达中国传感器科技信息网：<http://www.sensor-ic.com/>

商斯达工控安防网：<http://www.pc-ps.net/>

商斯达电子元器件网：<http://www.sunstare.com/>

商斯达微波光电产品网：[HTTP://www.rfoe.net/](http://www.rfoe.net/)

商斯达消费电子产品网：<http://www.icasic.com/>

商斯达实业科技产品网：<http://www.sunstars.cn/> 微波元器件销售热线：

地址：深圳市福田区福华路福庆街鸿图大厦 1602 室

电话：0755-82884100 83397033 83396822 83398585

传真：0755-83376182 (0) 13823648918 MSN: SUNS8888@hotmail.com

邮编：518033 E-mail:szss20@163.com QQ: 195847376

深圳赛格展销部：深圳华强北路赛格电子市场 2583 号 电话：0755-83665529 25059422

技术支持：0755-83394033 13501568376

欢迎索取免费详细资料、设计指南和光盘；产品凡多，未能尽录，欢迎来电查询。

北京分公司：北京海淀区知春路 132 号中发电子大厦 3097 号

TEL: 010-81159046 82615020 13501189838 FAX: 010-62543996

上海分公司：上海市北京东路 668 号上海赛格电子市场 D125 号

TEL: 021-28311762 56703037 13701955389 FAX: 021-56703037

西安分公司：西安高新开发区 20 所(中国电子科技集团导航技术研究所)

西安劳动南路 88 号电子商城二楼 D23 号

TEL: 029-81022619 13072977981 FAX:029-88789382