

QUARTZ CRYSTAL OSCILLATOR

GENERAL DESCRIPTION

The NJU6392 series is a 3V operation C-MOS quartz crystal oscillator which consists of an oscillation amplifier and a 3-state output buffer.

This series is classed into four versions A, B, C and P according to their oscillation frequency range mentioned in the line-up table.

The oscillation amplifier incorporates feed-back resistance and oscillation capacitors (C_g , C_d), therefore, it requires no external component except quartz crystal.


Drivability of the 3-state output buffer is 8mA (sink/source), thus it can drive C-MOS load.

FEATURES

- Low Operating Voltage. -- 2.4~3.6V
- Maximum Oscillation Frequency (See Line-Up Table)
- Low Operating Current
- High Fan-out -- $I_{OL}/I_{OH}=8mA$
- 3-state Output Buffer
- Oscillation Capacitors C_g and C_d on-chip
- Oscillation Output Stand-by Function
- Package Outline -- CHIP / EMP 8
- C-MOS Technology

LINE-UP TABLE


| Type No. | Recommended Osc. Freq. | Output Freq. | C_g/C_d |
|----------|------------------------|----------------|-----------|
| NJU6392A | 20~35MHz | f _o | 27pF |
| 6392B | 30~50MHz | | 19pF |
| 6392C | 45~75MHz | | 12/14pF |
| 6392P | ~75MHz | | No |

BLOCK DIAGRAM

PACKAGE OUTLINE


NJU6392XC



NJU6392XE

PAD LOCATION/PIN CONFIGURATION

COORDINATES

 Unit: μm

| No. | PAD | X | Y |
|-----|------|------|------|
| 1 | CONT | -408 | 248 |
| 2 | XT | -408 | 81 |
| 3 | XT | -408 | -86 |
| 4 | VSS | -408 | -248 |
| 5 | FOUT | 464 | -248 |
| 8 | VDD | 464 | 248 |

Chip Size : 1.29 X 0.8mm
 Chip Center : X=0 μm , Y=0 μm
 Chip Thickness : 400 $\mu m \pm 30 \mu m$
 (Note) No.6 and 7 terminals are only for package type information. There are no PAD on the chip.

■ TERMINAL DESCRIPTION

| NO. | SYMBOL | F U N C T I O N |
|-----|------------------|---|
| 1 | CONT | 3-State Output Control |
| | | CONT Output (F _{OUT}) |
| | | H or OPEN Output Frequency f _o |
| | | L Output High Impedance |
| 2 | XT | Quartz Crystal Connecting Terminals |
| 3 | XT | |
| 4 | V _{SS} | GND |
| 5 | F _{OUT} | Output frequency f _o |
| 8 | V _{DD} | + 3 V |

■ ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

| P A R A M E T E R | SYMBOL | R A T I N G S | UNIT |
|-----------------------------|-----------------|---|------|
| Supply Voltage | V _{DD} | -0.5 ~ +7.0 | V |
| Input Voltage | V _{IN} | V _{SS} -0.5 ~ V _{DD} +0.5 | V |
| Output Voltage | V _o | -0.5 ~ V _{DD} +0.5 | V |
| Input Current | I _{IN} | ±10 | mA |
| Output Current | I _o | ±25 | mA |
| Power Dissipation | P _d | 200 (EMP) | mW |
| Operating Temperature Range | Topr | -40 ~ +85 | °C |
| Storage Temperature Range | Tstg | -55 ~ +125 | °C |

(Note) Decoupling capacitor should be connected between V_{DD}-V_{SS} due to the stabilized operation for the circuit.

■ ELECTRICAL CHARACTERISTICS

 (Ta=25°C, V_{DD}=3V)

| P A R A M E T E R | SYMBOL | C O N D I T I O N S | MIN | TYP | MAX | UNIT |
|--------------------------------|--------------------------------|---|-----|-------|------|------|
| Operating Voltage | V _{DD} | | 2.4 | | 3.6 | V |
| Operating Current | I _{DD1} | A Version f _{osc} =24MHz, No Load | | 6 | 15 | mA |
| | I _{DD2} | B Version f _{osc} =48MHz, No Load | | 9 | 20 | |
| | I _{DD3} | C Version f _{osc} =48MHz, No Load (Note 1) | | 9 | 25 | |
| Stand-by Current | I _{st} | CONT, XT=V _{SS} , No Load (Note 2) | | | 1 | μA |
| Input Voltage | V _{IH} | | 2.4 | | 3.0 | V |
| | V _{IL} | | 0 | | 0.6 | |
| Output Current | I _{OH} | V _{OH} =2.7V | 8 | | | mA |
| | I _{OL} | V _{OL} =0.3V | 8 | | | |
| Input Current | I _{IN} | CONT Terminal, CONT=V _{SS} | 75 | 150 | 300 | μA |
| 3-St Off-leakage Current | I _{oz} | CONT=V _{SS} , F _{OUT} =V _{SS} or V _{DD} | | | ±0.1 | μA |
| Internal Capacitor (Note 3) | C _g /C _d | A Version f _{osc} =24MHz, No Load | | 27 | | pF |
| | | B Version f _{osc} =48MHz, No Load | | 19 | | |
| | | C Version f _{osc} =48MHz, No Load | | 12/14 | | |
| Max. Oscillation Freq. | f _{MAX} | A Version | 35 | | | MHz |
| | | B Version | 50 | | | |
| | | C/P Version (Note 1) | 75 | | | |
| Output Signal Symmetry | SYM | C _L =15pF at 1.5V C _L =30pF at 1.5V | 45 | 50 | 55 | % |
| Output Signal Rise Time | t _{r1} | C _L =15pF, 10~90% | | 2 | 4 | ns |
| | t _{r2} | C _L =30pF, 10~90% | | | 6 | |
| Output Signal Fall Time | t _{f1} | C _L =15pF, 90~10% | | 2 | 4 | ns |
| | t _{f2} | C _L =30pF, 90~10% | | | 6 | |



(Note 1) Only P Version is measured with external capacitors contained 3pF for C_g and 3pF for C_d.

(Note 2) Excluding input current on CONT terminal.



(Note 3) P Version is not mentioned due to internal oscillation capacitors C_g and C_d separated.

MEASUREMENT CIRCUITS

(1) Output Signal Symmetry


4

(2) Output Signal Rise / Fall Time



NJU6392 Series

MEMO

[CAUTION]

The specifications on this databook are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.