


PO Box 115, 17 Karrville Road  
Port Murray, NJ 07865  
Telephone 908-835-1720  
Fax 908-835-0002  
E-mail sales@flexcoMW.com  
http://www.FlexcoMW.com



## FCH95 Flexible Coaxial Cable 10 GHz Cable


### Frequency vs. Attenuation



#### Electrical Characteristics:

- Nominal Impedance: 50Ω
  - Velocity of Propagation: 91.8%
  - Effective Dielectric Constant: 1.185
  - Time Delay: 1.11 ns/ft
  - Shielding Effectiveness: -90 dBc min.
  - Dielectric Withstanding Voltage: 3.0 KV  
(@ 60 Hz, Sea Level/25°C)
  - Nominal Capacitance: 24 pF/ft
  - Maximum VSWR:
    - Precision Straight connectors:
      - DC - <4 GHz 1.10:1
      - 4 GHz - <8 GHz 1.15:1
      - 8 GHz - <10 GHz 1.25:1
    - Non-Precision or Angle connectors:
      - DC - <4 GHz 1.20:1
      - 4 GHz - <8 GHz 1.30:1
      - 8 GHz - 10 GHz 1.40:1
  - Maximum Frequency: 10.5 GHz
- For phase and other electrical characteristics, please consult the appropriate section of catalog.*

Frequency (GHz)	Maximum Insertion Loss (dB/ft)	Typical Insertion Loss (dB/ft)	Precision Connector Loss (dB)	Non Precision Connector Loss (dB)
0.5	0.03	0.03	0.02	0.03
1.0	0.04	0.04	0.02	0.03
2.0	0.05	0.05	0.03	0.05
3.0	0.07	0.07	0.04	0.06
4.0	0.08	0.07	0.04	0.06
5.0	0.09	0.08	0.05	0.08
6.0	0.10	0.09	0.06	0.09
7.0	0.11	0.10	0.06	0.09
8.0	0.12	0.11	0.07	0.11
9.0	0.12	0.11	0.08	0.12
10.0	0.13	0.12	0.08	0.12



#### Physical Characteristics:

- Center Conductor: Stranded SPC per ASTM-B8
- Dielectric: PTFE per L-P-403
- Outer Conductor: Strip wound oxygen free  
0.560" max. O.D.
- Braid: Bronze per UNS C22000, 0.600" max. O.D.
- Minimum Internal Bend Radius: 4 inches
- Operating Temperature: -60°C to +175°C
- Weight per Foot (unjacketed): 0.215 lbs
- Connector Interface: Per MIL-C-39012

#### Optional Jacketing and Braid

- Polyolefin per MIL-I-23053/5: 0.650" max. O.D.
- Neoprene per MIL-I-23053/1: 0.680" max. O.D.
- FEP per MIL-I-23053/11: 0.640" max. O.D.
- Nomex Braid: 0.655" max. O.D.