


Sensor---RI-02 Series



RI-02 Series


Ultra-miniature dry-switch hermetically sealed in a gas-filled envelope. Single-pole ,single-throw (SPST) type, having normally open contacts, and containing two magnetically actuated reeds .

The switch is of the double-ended type and may be actuated by an electromagnet ,a permanent magnet or combination of both.

The device is intended for use in relays, sensors, pulse counters or similar devices.

RI-02 Series Features

- &Ideal for General Purpose reed relays and sensors
- &Contact layers: ruthenium on gold
- &Superior glass-to-metal seal and blade alignment



Dimensions in inches (mm)

General data for all models RI-02

AT-Customization / Preformed Leads

Besides the standard models, customized products can also be supplied offering the following options:

- Operate and release ranges to customer specification
- Cropped and/or preformed leads

Coils

All characteristics are measured using the Philips standard coil. For definitions of the Philips Standard Coil, refer to "Application Notes" in the *Reed Switch Technical & Application Information* Section of this catalog.

Life expectancy and reliability

The life expectancy data given below are valid for a coil energized at 1.25 times the published maximum operate value for each type in the RI-02 series.

No-load conditions (operating frequency: 100Hz)

Life expectancy: min. 10^8 operations with a failure rate of less than 2×10^{-10} with a confidence level of 90%. End of life criteria:

Contact resistance $>1\Omega$ after 2 ms

Release time > 2 ms (latching or contact sticking)

Loaded conditions (resistive load: 5V; 100 mA; Operating frequency :125Hz

Life expectancy: min. 2×10^6 operations with a failure rate of less than 10^{-8} with a confidence level of 90%. End of life criteria:

●Contact resistance $>1\Omega$ after 2.5ms

●Release time >1 ms (latching or contact sticking).

Loaded conditions (resistive load: 20V; 500 mA; Operating frequency :125Hz

Life expectancy: min 2×10^6 operations with a failure rate of $<10^{-7}$ with a confidence level of 90%.

End of life criteria:

●Contact resistance $>2\Omega$ after 2.5 ms

●Release time >2.5 ms (latching or contact sticking).

Switching different loads involves different life expectancy and reliability data. Further information is available on request.

Sensor---RI-02 Series

Model Number

RI-02

Parameters

Test

Units

Operating Characteristics			
Operate Rangs		AT	7-21
Release Range		AT	3-16
Operate Time-including bounce (typ.)	(energization)	ms	0.30(25AT)
Bounce Time (typ)	(energization)	ms	0.10(25AT)
Release Time (mas)	(energization)	us	70(25AT)
Resonant Frequency (typ.)		Hz	10800
Electrical Characteristics			
Switch Power (max)		W	10
Switch Voltage DC (max)		V	200
Switch Voltage AC ,RMS value (max)		V	140
Switch Current DC (max)		mA	500
Switch Current AC, RMS value (max)		mA	500
Carry Current DC (max)		A	0.5
Breakdown Voltage (min)		V	200-230
Contact Resistance (initial max)	(energization)	mΩ	150(25AT)
Contact Resistance (inital typ.)	(energization)	mΩ	120(25AT)
Contact Capacitance (max)	without test coil	pF	0.30
Insulation Resistance (min)	RH≤45%	MΩ	10 ⁶

Mechanical Data

Contact arrangement is normally open; lead finish is tinned; net mass is approximately 90mg; and can be mounted in any position.

Shock

The switches are tested in accordance with "IEC 68-2-27", test Ea (peak acceleration 150 G, half sinewave; duration 11 ms). Such a shock will not cause an open switch (no magnetic field present) to close nor a switch kept closed by an 80 AT coil to open.

Vibration

The switches are tested in accordance with "IEC 68-2-26", test Fc (acceleration 10G; below cross-over frequency 57 to 62 Hz; amplitude 0.75 mm; frequency range 10 to 2000 Hz; duration 90 minutes.) Such a vibration will not cause an open switch (no magnetic field present) to close, nor a switch kept closed by an 80 AT coil to open.

Mechanical Strength

The robustness of the terminations is tested in accordance with "IEC 68-2-21", test Ua₁ (load 10 N).

Operating and Storage Temperature

Operating ambient temperature; min: -55°C; max: +125°C, Storage temperature; min: -55°C; max: +125°C. Note: Temperature excursions up to 150°C may be permissible. For more information contact your nearest Coto Technology sales office.

Soldering

The switch can withstand soldering heat in accordance with "IEC 68-2-20", test Tb, method 1B: solder bath at 350 ±10° C for 3.5 ±0.5 s. Solderability is tested in accordance with "IEC 68-2-20" test Ta, method 3: solder globule temperature 235°C; ageing 1b: 4 hours steam.

Welding

The leads can be welded.

Mounting

The leads should not be bent closer than 1 mm to the glass-to-metal seals. Stress on the seals should be avoided. Care must be taken to prevent stray magnetic fields from influencing the operating and measuring conditions.