

PLASTIC MELT PRESSURE TRANSDUCER / TRANSMITTER KITS

The GP:50 product line of melt pressure transducers and transmitters is based on the proven bonded strain gauge principle successfully utilized in thousands of applications. Our unique design incorporates a heavier sensor allowing a thicker tip diaphragm, provides better linearity, and reduces costs.

The design incorporates an extremely small capillary tubing that transmits the media pressure to the strain gauge sensor and mating electronics via a mechanical fill fluid. (Mercury is the standard, Silicone oil, Mineral oil and Nak are readily available depending on the application).

GP:50 Melt-Kits come with everything you need for efficient and reliable extrusion pressure measurement. Melt-Kits include transducer, cable, indicator and more.

STARTER MELT KIT:

Ideal for processors currently using blow plugs

- Model 30 pressure transducer
- 1211-B-B-1-R melt pressure indicator
- · MECA-CA connecting cable
- MHK-AA transducer mounting hole machining tool kit
- · Getting started guide
- Tube of anti-sieze compound
- Screwdriver
- · GP:50 baseball hat



Seen here with Model 30

CLASSIC MELT KIT:

Ideal for processors currently measuring pressure

- Model 30 or Model 31 transducer
- 1211-B-B-1-R melt pressure indicator
- MECA-CA connecting cable
- · Getting started guide
- Tube of anti-sieze compound
- Screwdriver
- GP:50 baseball hat



Seen here with Model 31

TEMPERATURE / PRESSURE MELT KIT:

Ideal for processors with temperature and pressure measurement requirements

- Model 35 temperature/pressure transducer
- 1290 indicator
- MECA-CA connecting cable
- MTC-AA thermocouple connector
- Getting started guide
- Tube of anti-sieze compound
- Screwdriver
- GP:50 baseball hat



DIFFERENTIAL MELT KIT:

Ideal for processors who measure and control differential pressure

- Two 131 or two 331 pressure transducers
- 1235 process controller
- Two MECA-CA connecting cables
- · Getting started guide
- Tube of anti-sieze compound
- Screwdriver
- GP:50 baseball hat



ORDERING GUIDE: Model • Transducer • Range • Options

| Starter Melt-Kit Model 1310 | Classic Melt-Kit Model 1311 | Temperature / Pressure Melt-Kit Model 1312 | Differential Melt-Kit Model 1313 |
|--|---|--|---|
| Ex: 1310-130-RX-AA | Ex: 1311-130-RX-AA | Ex: 1312-135-RX-AA | Ex: 1313-131-RX-AA |
| Transducer 130 3.3 mV/V 230 5 Vdc 330 4-20 mA | Transducer 130 3.3 mV/V 230 5 Vdc 330 4-20 mA 131 3.3 mV/V 231 5 mV/V 331 4-20 mA | Transducer 135 3.3 mV/V 235 5 Vdc 335 4-20 mA | Transducer 131 3.3 mV/V 331 4-20 mA |

Consult factory for additional options.

Pressure Ranges (PSI)

> RH 500 RK 750 RM 1000 RO 1500 RT 3000 RV 5000 RX 7500 RZ 10000