

Products & Services

Aluminum single point load cell



AG 1 kg ... 100 kg

- Aluminum construction, IP65 protection level
- Approved up to 2 000 d OIML R60 for capacities up to 2.5 kg
- Approved up to 6 000 d OIML R60 and 5 000 d NTEP for capacities from 5 to 100 kg
- Maximum platform size up to 400x400 mm
- Ideally suited for single-cell scales or dosing machines
- Capacities: 1, 2.5, 5, 10, 15, 20, 30, 50, 75, 100 kg



DOWNLOADS

Product datasheets

AG - 1 kg ... 2.5 kg
AG load cell datasheet
, FULLHTML);"
onmouseout="return nd();" ">FT-AG2,5-FE-0708.pdf

AG - 5 kg ... 100 kg
AG load cell datasheet
, FULLHTML);" onmouseout="return nd();" ">FT-AG100-FE-0708.pdf

AG100 C6 - 5 kg ... 100 kg
AG100 C6 loadcell data sheet
, FULLHTML);" onmouseout="return nd();" ">FT-AG100-C6-FE-0708.pdf

ACCESSORIES

Damping kit for AG



SPEEDCELL-AG 5 kg ... 50 kg

- Approved up to 3 000 d OIML R60
- Damping kit designed for accurate high speed weighing
- Fluid damping performed by a guaranteed "leak free" device
- Increases the weighing frequency by up to 10 times
- Capacities : 5, 10, 15, 20, 30 kg



DOWNLOADS

Product datasheets

SPEEDCELL AG - 5 kg ... 50 kg
AG load cell with SPEEDCELL mounting datasheet
, FULLHTML);"
onmouseout="return nd();" ">FT-SPEEDCELL-AG-FE-0806.p...

SERVICES

Weighing calibration



Calibration kg 500 g ... 20 t

- High level of accuracy and very limited incertitude
- 500 g to 6 t by load cell in tension, 500 g à 20 t in compression
- Multi-cell calibration capabilities, corner adjustment
- Mass and test means linked to the International standards
- 5 tons direct dead weights machine with temperature chamber
- 25 tons dead weights level machine with temperature chamber

DOWNLOADS

Product datasheets

Calibration
Calibration services datasheet
, FULLHTML);"
onmouseout="return nd();" ">FT-ETAL-FE-0404.pdf