


Section 6

Waveguide to Coax Adapters




Waveguide to Coax Adapters

Frequency GHz	Model Number	VSWR Maximum	A Max.	B Max.	C Max.	Connectors	
						Male	Female
26.5-40.0	28AC206	<1.30	.52	.52	.35		2.9mm
26.5-40.0	28AC216	<1.35	.52	.63	.35	2.9mm	
22.0-33.0	34AC206	<1.25	.62	.54	.40		2.9mm
22.0-33.0	34AC216	<1.25	.62	.63	.40	2.9mm	
18.0-26.5	42AC206	<1.25	.62	.54	.40		SMA
18.0-26.5	42AC216	<1.15	.62	.54	.40		2.9mm
18.0-26.5	42AC226	<1.15	.62	.57	.40		3.5mm
18.0-26.5	42AC236	<1.25	.62	.65	.40	SMA	
15.0-22.0	51AC206	<1.25	.67	.59	.43		SMA
12.4-18.0	62AC206	<1.25	.79	.62	.50		SMA
10.0-15.0	75AC206	<1.25	.90	.68	.55		SMA
10.0-15.0	75AC216	<1.15	.90	.68	.55		SMA
8.2-12.4	90AC206	<1.25	1.02	.69	.62		SMA



Male



Female