

普通矩形波导 D 型法兰盘的尺寸

法兰盘型号 FDM、FDP		14	18	22	26	32	40	48	58	70	
IEC 法兰盘型号 FDR、UDR		14	18	22	26	32	40	48	58	70	
相配的波导型号		BJ14	BJ18	BJ22	BJ26	BJ32	BJ40	BJ48	BJ58	BJ70	
图		图 22	图 22	图 22	图 22	图 22	图 22	图 23	图 23	图 23	
孔的 尺寸	基本直径 A	8.00	8.00	6.35	6.35	6.35	6.35	6.35	6.35	5.00	
	定位孔	配合符号	A9	A9	A9	A9	A9	B9	B9	B9	B9
		偏差	下	+.280	+.280	+.280	+.280	+.280	+.150	+.150	+.150
	上		+.316	+.316	+.316	+.316	+.316	+.186	+.186	+.186	+.170
	边接孔	配合符号	A15	A15	A15	A15	A15	B15	B15	B15	B15
		偏差	下	+.282	+.282	+.282	+.282	+.282	+.150	+.150	+.150
上	+.860		+.860	+.860	+.860	+.860	+.730	+.730	+.730	+.620	
a		165.10	129.54	109.22	86.36	72.14	58.17	47.549	40.386	34.849	
b		82.55	64.77	54.61	43.18	34.04	29.08	22.149	20.193	15.799	
a1		169.16	133.60	113.28	90.42	76.20	61.42	50.80	43.64	38.10	
b1		86.61	68.83	58.67	47.24	38.10	32.33	25.40	23.44	19.05	
p		220.70	185.00	161.10	138.10	114.30	98.4	88.9	81.0	68.3	
N		138.10	120.00	106.40	95.30	76.20	69.90	63.50	61.90	49.20	
x		12.09	12.09	12.09	12.09	10.06	10.06	10.06	10.05	10.05	
y		0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	
Rmax		0.6	0.6	0.6	0.6	0.6	0.5	0.5	0.5	0.5	
R1		8	8	8	8	6	6	6	6	4	
R2		3.65	3.65	3.65	3.65	2.40	2.40	2.40	2.40	1.80	
C		120.600	100.08	90.78	68.28	65.08	54.36	28.58	25.40	22.22	
D		200.00	165.00	141.98	119.06	97.22	82.30	71.82	64.66	55.58	
E		63.46	50.04	47.64	34.08	29.36	25.40	22.22	19.04	15.88	
F		117.38	100.08	87.38	76.20	59.14	53.34	46.44	44.46	36.52	
ΦZ		0.20	0.20	0.20	0.20	0.20	0.10	0.10	0.10	0.10	
G	基本尺寸	210.7	175.0	151.1	128.1	106.3	90.4	80.9	73.0	63.3	
	偏差	±0.50	±0.50	±0.50	±0.50	±0.40	±0.40	±0.40	±0.40	±0.30	

