

Inductors

For General Applications

Radial

EL Series EL0607 Type

FEATURES

- The EL series inductors are available in 6 form factors ranging from 0304 to 0909.
- With a miniature winding construction, these inductors nonetheless achieve high Q characteristics.
- Available in tape packaging to support automated mounting machines.

APPLICATIONS

Televisions, VCRs, personal computers, and other electronic equipment.

SPECIFICATIONS

Operating temperature range	−20 to +80°C [Including self-temperature rise]
Storage temperature range	−40 to +80°C [Unit of products]
Terminal tensile strength	EL0304: 4.9N min. EL0305: 7.84N min. EL0405: 7.84N min. EL0606: 14.7N min. EL0607: 14.7N min. EL0909: 14.7N min.

PRODUCT IDENTIFICATION

EL	0405	RA-	1R0	K	-3
(1)	(2)	(3)	(4)	(5)	(6)

(1)Series name

(2)Dimensions

0304	4×3×4mm (lead pitch 2.5mm)
0305	5×3.8×5mm (lead pitch 5mm)
0405	5.4×4.4×7mm (lead pitch 5mm)
0606	6.4×6×10mm (lead pitch 5mm)
0607	7.4×6.2×10mm (lead pitch 5mm)
0909	9.4×9×13.5mm (lead pitch 5mm)

(3)Packaging style

RA	Ammo-pack
RR	Reel

(4)Inductance value

R22	0.22μH
1R0	1μH

(5)Inductance tolerance

J	±5%
K	±10%
M	±20%

(6)TDK internal code

(Some products may not have this number. See the main body for details.)

PACKAGING STYLE AND QUANTITIES


Packaging style	Type	Quantity
Ammo-pack	EL0304RA	3000 pieces
	EL0305RA	3000 pieces
	EL0405RA	3000 pieces
	EL0606RA	2000 pieces
	EL0607RA	2000 pieces
Taping	EL0909RR	500 pieces/reel

Inductors

For General Applications
Radial

EL Series EL0607 Type

AMMO-PACK TAPING STYLE SHAPES AND DIMENSIONS



CHARACTERISTICS

Operating temperature range	-20 to +80°C [Including self-temperature rise 20°C max.]
Withstand voltage Erms	250V
Rated current	Based on inductance change [-10% to the initial value]
Terminal tensile strength	14.7N min.
Moisture resistance	$\Delta L/L \leq \pm 5\%$ $\Delta Q/Q \leq \pm 25\%$

ELECTRICAL CHARACTERISTICS

Inductance (μH)	Inductance tolerance	Q min.	Test frequency L, Q(MHz)	Self-resonant frequency (MHz)min.	DC resistance (Ω)max.	Rated current (mA)max.	Part No.
10	±10, ±5%	20	2.52	17	0.19	780	EL0607RA-100X*
12	±10, ±5%	20	2.52	14	0.22	730	EL0607RA-120X
15	±10, ±5%	20	2.52	12	0.24	650	EL0607RA-150X
18	±10, ±5%	20	2.52	10.5	0.26	610	EL0607RA-180X
22	±10, ±5%	20	2.52	10	0.29	540	EL0607RA-220X
27	±10, ±5%	20	2.52	9.5	0.32	480	EL0607RA-270X
33	±10, ±5%	20	2.52	8.5	0.34	440	EL0607RA-330X
39	±10, ±5%	20	2.52	8	0.42	410	EL0607RA-390X
47	±10, ±5%	20	2.52	7	0.47	375	EL0607RA-470X
56	±10, ±5%	20	2.52	6.8	0.52	340	EL0607RA-560X
68	±10, ±5%	15	2.52	6.5	0.58	320	EL0607RA-680X
82	±10, ±5%	15	2.52	6.3	0.64	285	EL0607RA-820X
100	±10, ±5%	25	0.796	6	0.85	260	EL0607RA-101X
120	±10, ±5%	25	0.796	5.4	1	240	EL0607RA-121X
150	±10, ±5%	25	0.796	4.75	1.2	215	EL0607RA-151X
180	±10, ±5%	30	0.796	4	1.5	195	EL0607RA-181X
220	±10, ±5%	30	0.796	3.85	1.65	180	EL0607RA-221X
270	±10, ±5%	30	0.796	3.6	2.15	160	EL0607RA-271X
330	±10, ±5%	35	0.796	3.3	2.9	145	EL0607RA-331X
390	±10, ±5%	35	0.796	3	3.25	135	EL0607RA-391X
470	±10, ±5%	35	0.796	2.8	4.05	125	EL0607RA-471X
560	±10, ±5%	40	0.796	2.4	4.45	115	EL0607RA-561X
680	±10, ±5%	40	0.796	2.2	5.85	105	EL0607RA-681X
820	±10, ±5%	40	0.796	2	6.6	90	EL0607RA-821X
1000	±10, ±5%	45	0.252	1.8	8.9	85	EL0607RA-102X
1200	±10, ±5%	45	0.252	1.7	10.5	75	EL0607RA-122X
1500	±10, ±5%	45	0.252	1.5	11.9	70	EL0607RA-152X
1800	±10, ±5%	45	0.252	1.3	16.5	60	EL0607RA-182X
2200	±10, ±5%	45	0.252	1.2	19	58	EL0607RA-222X
2700	±10, ±5%	40	0.252	0.8	32	52	EL0607RA-272X

* X: Please specify inductance tolerance, K(±10%) or J(±5%)

Inductors

For General Applications
Radial

EL Series EL0607 Type

AMMO-PACK TAPING STYLE


ELECTRICAL CHARACTERISTICS

Inductance (μH)	Inductance tolerance	Q min.	Test frequency L, Q(MHz)	Self-resonant frequency (MHz)min.	DC resistance (Ω)max.	Rated current (mA)max.	Part No.
3300	±10, ±5%	40	0.252	0.7	34	48	EL0607RA-332X*
3900	±10, ±5%	40	0.252	0.7	38	45	EL0607RA-392X
4700	±10, ±5%	40	0.252	0.6	56	40	EL0607RA-472X
5600	±10, ±5%	40	0.252	0.5	63	37	EL0607RA-562X
6800	±10, ±5%	40	0.252	0.4	70	34	EL0607RA-682X
8200	±10, ±5%	40	0.252	0.4	77	31	EL0607RA-822X
10000	±10, ±5%	25	0.0796	0.3	95	28	EL0607RA-103X
12000	±10, ±5%	25	0.0796	0.2	110	25	EL0607RA-123X
15000	±10, ±5%	20	0.0796	0.1	160	21	EL0607RA-153X


* X: Please specify inductance tolerance, K(±10%) or J(±5%)

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE CHANGE vs. DC SUPERPOSITION CHARACTERISTICS




INDUCTANCE CHANGE vs. TEMPERATURE CHARACTERISTICS



Test terminal: Measuring at after the correction
Cycle: +20°C → +85°C → +20°C → -20°C
Temperature: Kept stabilized for 30+5, -0min each

Q vs. FREQUENCY CHARACTERISTICS



SUNSTAR 商斯达实业集团是集研发、生产、工程、销售、代理经销、技术咨询、信息服务等为一体的高科技企业，是专业高科技电子产品生产厂家，是具有 10 多年历史的专业电子元器件供应商，是中国最早和最大的仓储式连锁规模经营大型综合电子零部件代理分销商之一，是一家专业代理和分销世界各大品牌 IC 芯片和电子元器件的连锁经营综合性国际公司，专业经营进口、国产名厂名牌电子元件，型号、种类齐全。在香港、北京、深圳、上海、西安、成都等全国主要电子市场设有直属分公司和产品展示展销窗口门市部专卖店及代理分销商，已在全国范围内建成强大统一的供货和代理分销网络。我们专业代理经销、开发生产电子元器件、集成电路、传感器、微波光电元器件、工控机/DOC/DOM 电子盘、专用电路、单片机开发、MCU/DSP/ARM/FPGA 软件硬件、二极管、三极管、模块等，是您可靠的一站式现货配套供应商、方案提供商、部件功能模块开发配套商。商斯达实业公司拥有庞大的资料库，有数位毕业于著名高校——有中国电子工业摇篮之称的西安电子科技大学（西军电）并长期从事国防尖端科技研究的高级工程师为您精挑细选、量身订做各种高科技电子元器件，并解决各种技术问题。

微波光电部专业代理经销高频、微波、光纤、光电元器件、组件、部件、模块、整机；电磁兼容元器件、材料、设备；微波 CAD、EDA 软件、开发测试仿真工具；微波、光纤仪器仪表。欢迎国外高科技微波、光纤厂商将优秀产品介绍到中国、共同开拓市场。长期大量现货专业批发高频、微波、卫星、光纤、电视、CATV 器件：晶振、VCO、连接器、PIN 开关、变容二极管、开关二极管、低噪晶体管、功率电阻及电容、放大器、功率管、MMIC、混频器、耦合器、功分器、振荡器、合成器、衰减器、滤波器、隔离器、环行器、移相器、调制解调器；光电子器件和组件：红外发射管、红外接收管、光电开关、光敏管、发光二极管和发光二极管组件、半导体激光二极管和激光器组件、光电探测器和光接收组件、光发射接收模块、光纤激光器和光放大器、光调制器、光开关、DWDM 用光发射和接收器件、用户接入系统光收发器件与模块、光纤连接器、光纤跳线/尾纤、光衰减器、光纤适配器、光隔离器、光耦合器、光环行器、光复用器/转换器；无线收发芯片和模组、蓝牙芯片和模组。

更多产品请看本公司产品专用销售网站：

商斯达微波光电产品网：[HTTP://www.rfoe.net/](http://www.rfoe.net/)

商斯达中国传感器科技信息网：<http://www.sensor-ic.com/>

商斯达工控安防网：<http://www.pc-ps.net/>

商斯达电子元器件网：<http://www.sunstare.com/>

商斯达消费电子产品网：<http://www.icasic.com/>

商斯达实业科技产品网：<http://www.sunstars.cn/> 射频微波光电元器件销售热线：

地址：深圳市福田区福华路福庆街鸿图大厦 1602 室

电话：0755-83396822 83397033 83398585 82884100

传真：0755-83376182 (0) 13823648918 MSN: SUNS8888@hotmail.com

邮编：518033 E-mail:szss20@163.com QQ: 195847376

深圳赛格展销部：深圳华强北路赛格电子市场 2583 号 电话：0755-83665529 25059422

技术支持：0755-83394033 13501568376

欢迎索取免费详细资料、设计指南和光盘；产品凡多，未能尽录，欢迎来电查询。

北京分公司：北京海淀区知春路 132 号中发电子大厦 3097 号

TEL: 010-81159046 82615020 13501189838 FAX: 010-62543996

上海分公司：上海市北京东路 668 号上海赛格电子市场 D125 号

TEL: 021-28311762 56703037 13701955389 FAX: 021-56703037

西安分公司：西安高新开发区 20 所(中国电子科技集团导航技术研究所)

西安劳动南路 88 号电子商城二楼 D23 号

TEL: 029-81022619 13072977981 FAX:029-88789382