


DATA SHEET



BYD73 series

Ultra fast low-loss controlled avalanche rectifiers

Product specification

1996 Sep 18

Supersedes data of 1996 May 24

Ultra fast low-loss controlled avalanche rectifiers

BYD73 series

FEATURES


- Glass passivated
- High maximum operating temperature
- Low leakage current
- Excellent stability
- Guaranteed avalanche energy absorption capability
- Available in ammo-pack.

DESCRIPTION

Cavity free cylindrical glass SOD81 package through Implotec™⁽¹⁾ technology. This package is

hermetically sealed and fatigue free as coefficients of expansion of all used parts are matched.

(1) Implotec is a trademark of Philips.



MAM123

Fig.1 Simplified outline (SOD81) and symbol.

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{RRM}	repetitive peak reverse voltage		–	50	V
	BYD73A			100	V
	BYD73B			150	V
	BYD73C			200	V
	BYD73D			250	V
	BYD73E			300	V
	BYD73F			400	V
V_R	continuous reverse voltage		–	50	V
	BYD73A			100	V
	BYD73B			150	V
	BYD73C			200	V
	BYD73D			250	V
	BYD73E			300	V
	BYD73F			400	V
$I_{F(AV)}$	average forward current	$T_{tp} = 55^\circ\text{C}$; lead length = 10 mm; see Figs 2 and 3; averaged over any 20 ms period; see also Figs 10 and 11	–	1.75	A
	BYD73A to D			1.70	A
	BYD73E to G				
$I_{F(AV)}$	average forward current	$T_{amb} = 60^\circ\text{C}$; PCB mounting (see Fig.16); see Figs 4 and 5; averaged over any 20 ms period; see also Figs 10 and 11	–	1.00	A
	BYD73A to D			0.95	A
	BYD73E to G				

Ultra fast low-loss controlled avalanche rectifiers

BYD73 series

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
I_{FRM}	repetitive peak forward current BYD73A to D BYD73E to G	$T_{tp} = 55^\circ\text{C}$; see Figs 6 and 7	— —	14 15	A A
I_{FRM}	repetitive peak forward current BYD73A to D BYD73E to G	$T_{amb} = 60^\circ\text{C}$; see Figs 8 and 9	— —	8.5 9.5	A A
I_{FSM}	non-repetitive peak forward current	$t = 10 \text{ ms half sine wave};$ $T_j = T_{j\max}$ prior to surge; $V_R = V_{RRM\max}$	—	25	A
E_{RSM}	non-repetitive peak reverse avalanche energy	$L = 120 \text{ mH}; T_j = T_{j\max}$ prior to surge; inductive load switched off	—	10	mJ
T_{stg}	storage temperature		—65	+175	°C
T_j	junction temperature		—65	+175	°C

ELECTRICAL CHARACTERISTICS

 $T_j = 25^\circ\text{C}$ unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_F	forward voltage BYD73A to D BYD73E to G	$I_F = 1 \text{ A}; T_j = T_{j\max}$; see Figs 12 and 13	— —	— —	0.75 0.83	V V
V_F	forward voltage BYD73A to D BYD73E to G	$I_F = 1 \text{ A};$ see Figs 12 and 13	— —	— —	0.98 1.05	V V
$V_{(BR)R}$	reverse avalanche breakdown voltage BYD73A BYD73B BYD73C BYD73D BYD73E BYD73F BYD73G	$I_R = 0.1 \text{ mA}$	55 110 165 220 275 330 440	— — — — — — —	— — — — — — —	V V V V V V V
I_R	reverse current	$V_R = V_{RRM\max}$; see Fig.14	—	—	1	μA
		$V_R = V_{RRM\max}$; $T_j = 165^\circ\text{C}$; see Fig.14	—	—	100	μA
t_{rr}	reverse recovery time BYD73A to D BYD73E to G	when switched from $I_F = 0.5 \text{ A}$ to $I_R = 1 \text{ A}$; measured at $I_R = 0.25 \text{ A}$; see Fig.18	— —	— —	25 50	ns ns

Ultra fast low-loss controlled avalanche rectifiers

BYD73 series

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
C_d	diode capacitance BYD73A to D BYD73E to G	$f = 1 \text{ MHz}; V_R = 0 \text{ V};$ see Fig.15	—	50	—	pF
$ dI_R $ $ dt $	maximum slope of reverse recovery current BYD73A to D BYD73E to G	when switched from $I_F = 1 \text{ A}$ to $V_R \geq 30 \text{ V}$ and $dI_F/dt = -1 \text{ A}/\mu\text{s}$; see Fig.17	—	—	4	$\text{A}/\mu\text{s}$
			—	—	5	$\text{A}/\mu\text{s}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th j\text{-tp}}$	thermal resistance from junction to tie-point	lead length = 10 mm	60	K/W
$R_{th j\text{-a}}$	thermal resistance from junction to ambient	note 1	120	K/W


Note

1. Device mounted on an epoxy-glass printed-circuit board, 1.5 mm thick; thickness of Cu-layer $\geq 40 \mu\text{m}$, see Fig.16.
For more information please refer to the "General Part of associated Handbook".

Ultra fast low-loss controlled avalanche rectifiers

BYD73 series

GRAPHICAL DATA




BYD73A to D

a = 1.42; V_R = V_{RRMmax}; δ = 0.5.

Switched mode application.

Fig.2 Maximum permissible average forward current as a function of tie-point temperature (including losses due to reverse leakage).




BYD73E to G

a = 1.42; V_R = V_{RRMmax}; δ = 0.5.

Switched mode application.

Fig.3 Maximum permissible average forward current as a function of tie-point temperature (including losses due to reverse leakage).




BYD73A to D

a = 1.42; V_R = V_{RRMmax}; δ = 0.5.

Device mounted as shown in Fig.16.

Switched mode application.

Fig.4 Maximum permissible average forward current as a function of ambient temperature (including losses due to reverse leakage).



BYD73E to G

a = 1.42; V_R = V_{RRMmax}; δ = 0.5.


Device mounted as shown in Fig.16.

Switched mode application.

Fig.5 Maximum permissible average forward current as a function of ambient temperature (including losses due to reverse leakage).

Ultra fast low-loss controlled avalanche rectifiers

BYD73 series




BYD73A to D

$T_{tp} = 55^\circ C$; $R_{th\ j\cdot tp} = 60 \text{ K/W}$.

V_{RRMmax} during $1 - \delta$; curves include derating for $T_{j\ max}$ at $V_{RRM} = 200 \text{ V}$.

Fig.6 Maximum repetitive peak forward current as a function of pulse time (square pulse) and duty factor.



BYD73E to G


$T_{tp} = 55^\circ C$; $R_{th\ j\cdot tp} = 60 \text{ K/W}$.

V_{RRMmax} during $1 - \delta$; curves include derating for $T_{j\ max}$ at $V_{RRM} = 400 \text{ V}$.

Fig.7 Maximum repetitive peak forward current as a function of pulse time (square pulse) and duty factor.

Ultra fast low-loss controlled avalanche rectifiers

BYD73 series




BYD73A to D

$T_{amb} = 60^\circ\text{C}$; $R_{th\ j-a} = 120 \text{ K/W}$.

V_{RRMmax} during $1 - \delta$; curves include derating for $T_{j\ max}$ at $V_{RRM} = 200 \text{ V}$.

Fig.8 Maximum repetitive peak forward current as a function of pulse time (square pulse) and duty factor.



BYD73E to G


$T_{amb} = 60^\circ\text{C}$; $R_{th\ j-a} = 120 \text{ K/W}$.

V_{RRMmax} during $1 - \delta$; curves include derating for $T_{j\ max}$ at $V_{RRM} = 400 \text{ V}$.

Fig.9 Maximum repetitive peak forward current as a function of pulse time (square pulse) and duty factor.

Ultra fast low-loss controlled avalanche rectifiers


BYD73 series



BYD73A to D

$a = I_{F(RMS)} / I_{F(AV)}$; $V_R = V_{RRMmax}$; $\delta = 0.5$.


Fig.10 Maximum steady state power dissipation (forward plus leakage current losses, excluding switching losses) as a function of average forward current.



BYD73E to G

$a = I_{F(RMS)} / I_{F(AV)}$; $V_R = V_{RRMmax}$; $\delta = 0.5$.


Fig.11 Maximum steady state power dissipation (forward plus leakage current losses, excluding switching losses) as a function of average forward current.



BYD73A to D

Dotted line: $T_j = 175^\circ\text{C}$.
Solid line: $T_j = 25^\circ\text{C}$.

Fig.12 Forward current as a function of forward voltage; maximum values.




BYD73E to G

Dotted line: $T_j = 175^\circ\text{C}$.
Solid line: $T_j = 25^\circ\text{C}$.

Fig.13 Forward current as a function of forward voltage; maximum values.


Ultra fast low-loss controlled avalanche rectifiers

BYD73 series




V_R = V_{RRMmax}.

Fig.14 Reverse current as a function of junction temperature; maximum values.



f = 1 MHz; T_j = 25 °C.

Fig.15 Diode capacitance as a function of reverse voltage; typical values.



Dimensions in mm.

Fig.16 Device mounted on a printed-circuit board.






Fig.17 Reverse recovery definitions.

Ultra fast low-loss controlled avalanche rectifiers

BYD73 series



Input impedance oscilloscope: $1 \text{ M}\Omega$, 22 pF ; $t_r \leq 7 \text{ ns}$.


Source impedance: 50Ω ; $t_r \leq 15 \text{ ns}$.

Fig.18 Test circuit and reverse recovery time waveform and definition.

Ultra fast low-loss controlled avalanche rectifiers

BYD73 series

PACKAGE OUTLINE



Dimensions in mm.

The marking band indicates the cathode.

Fig.19 SOD81.

DEFINITIONS

Data Sheet Status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.

SUNSTAR 商斯达实业集团是集研发、生产、工程、销售、代理经销、技术咨询、信息服务等为一体的高科技企业，是专业高科技电子产品生产厂家，是具有 10 多年历史的专业电子元器件供应商，是中国最早和最大的仓储式连锁规模经营大型综合电子零部件代理分销商之一，是一家专业代理和分销世界各大品牌 IC 芯片和电子元器件的连锁经营综合性国际公司，专业经营进口、国产名厂名牌电子元件，型号、种类齐全。在香港、北京、深圳、上海、西安、成都等全国主要电子市场设有直属分公司和产品展示展销窗口门市部专卖店及代理分销商，已在全国范围内建成强大统一的供货和代理分销网络。我们专业代理经销、开发生产电子元器件、集成电路、传感器、微波光电元器件、工控机/DOC/DOM 电子盘、专用电路、单片机开发、MCU/DSP/ARM/FPGA 软件硬件、二极管、三极管、模块等，是您可靠的一站式现货配套供应商、方案提供商、部件功能模块开发配套商。商斯达实业公司拥有庞大的资料库，有数位毕业于著名高校——有中国电子工业摇篮之称的西安电子科技大学（西军电）并长期从事国防尖端科技研究的高级工程师为您精挑细选、量身订做各种高科技电子元器件，并解决各种技术问题。

微波光电部专业代理经销高频、微波、光纤、光电元器件、组件、部件、模块、整机；电磁兼容元器件、材料、设备；微波 CAD、EDA 软件、开发测试仿真工具；微波、光纤仪器仪表。欢迎国外高科技微波、光纤厂商将优秀产品介绍到中国、共同开拓市场。长期大量现货专业批发高频、微波、卫星、光纤、电视、CATV 器件：晶振、VCO、连接器、PIN 开关、变容二极管、开关二极管、低噪晶体管、功率电阻及电容、放大器、功率管、MMIC、混频器、耦合器、功分器、振荡器、合成器、衰减器、滤波器、隔离器、环行器、移相器、调制解调器；光电子元器件和组件：红外发射管、红外接收管、光电开关、光敏管、发光二极管和发光二极管组件、半导体激光二极管和激光器组件、光电探测器和光接收组件、光发射接收模块、光纤激光器和光放大器、光调制器、光开关、DWDM 用光发射和接收器件、用户接入系统光光收发器件与模块、光纤连接器、光纤跳线/尾纤、光衰减器、光纤适配器、光隔离器、光耦合器、光环行器、光复用器/转换器；无线收发芯片和模组、蓝牙芯片和模组。

更多产品请看本公司产品专用销售网站：

商斯达中国传感器科技信息网：<http://www.sensor-ic.com/>

商斯达工控安防网：<http://www.pc-ps.net/>

商斯达电子元器件网：<http://www.sunstare.com/>

商斯达微波光电产品网：<HTTP://www.rfoe.net/>

商斯达消费电子产品网：<http://www.icasic.com/>

商斯达实业科技产品网：<http://www.sunstars.cn/> 微波元器件销售热线：

地址：深圳市福田区福华路福庆街鸿图大厦 1602 室

电话：0755-82884100 83397033 83396822 83398585

传真：0755-83376182 (0) 13823648918 MSN：SUNS8888@hotmail.com

邮编：518033 E-mail：szss20@163.com QQ：195847376

深圳赛格展销部：深圳华强北路赛格电子市场 2583 号 电话：0755-83665529 25059422

技术支持：0755-83394033 13501568376

欢迎索取免费详细资料、设计指南和光盘；产品凡多，未能尽录，欢迎来电查询。

北京分公司：北京海淀区知春路 132 号中发电子大厦 3097 号

TEL：010-81159046 82615020 13501189838 FAX：010-62543996

上海分公司：上海市北京东路 668 号上海赛格电子市场 D125 号

TEL：021-28311762 56703037 13701955389 FAX：021-56703037

西安分公司：西安高新区 20 所(中国电子科技集团导航技术研究所)

西安劳动南路 88 号电子商城二楼 D23 号

TEL：029-81022619 13072977981 FAX:029-88789382